

Class 5 Assessment Weight Details for supplied vehicles.

If you are completing the Class 5 NZTA Approved Driver Licence Course using your own vehicle, your vehicle must meet all NZTA requirements:

- Current Certificate of Fitness and COF labels displayed on the windscreen.
- Current Road User Charges licence or E-road.
- Current vehicle licence displayed.

Assessment cannot take place if any of the above conditions are not met.

Vehicle combinations must be loaded as follows:

3 Axle Tractor Unit and Tri Axle Semi must be loaded to at least **29,000 kg**.



4 Axle Tractor Unit and Quad Axle Trailer must be loaded to at least **32,000 kg**.



3 Axle Tractor Unit and Quad Axle Trailer must be loaded to at least **31,000 kg**.



3 Axle Tractor Unit and Tandem Axle Trailer must be loaded to at least **31,000 kg**.



8 Axle B-Train Combination:

- Front trailer must weigh at least **16,000 kg**
- Second trailer must weigh at least **16,000 kg**.



9 Axle B-Train Combination:

- Front trailer must weigh at least **17,000 kg**
- Second trailer must weigh at least **17,000 kg**.



4 Axle Tractor Unit with Tri-Axle Trailer must be loaded to at least **31,000 kg**.



3 Axle Truck with 4 Axle Trailer:

- Truck must weigh at least **18,000 kg**
- Trailer must weigh at least **18,000 kg**.



4 Axle Truck with 4 Axle Trailer:

- Truck must weigh at least **19,000 kg**
- Trailer must weigh at least **18,000 kg**.



4 Axle Truck with 5 Axle Trailer:

- Truck must weigh at least **19,000 kg**
- Trailer must weigh at least **20,000 kg**.



3 Axle Truck with 3 Axle Trailer:

- Truck must weigh at least **18,000 kg**

- Trailer must weigh at least **16,000 kg**.



4 Axle Truck with 3 Axle Trailer:

- Truck must weigh at least **19,000 kg**
- Trailer must weigh at least **16,000 kg**.



Load Restraint Requirements

The load must be properly restrained to the requirements of the Truck Loading Code for the assessment to take place:

- The combined rated strength of all the restraints for loads baulked against the headboard must be equal to the weight of the load.
- For loads not against the headboard, the combined rated strength of all the restraints must be equal to twice the weight of the load.